


Duracraft®



OWNER'S MANUAL

4 Gallon (15.1 Litre) Output Per Day

**NATURAL COOL
MOISTURE™ HUMIDIFIER**

Model DH-831

IMPORTANT SAFETY INSTRUCTIONS

READ ALL INSTRUCTIONS BEFORE USING THIS HUMIDIFIER AND SAVE THESE IMPORTANT INSTRUCTIONS FOR EASY REFERENCE.

WHEN USING ANY ELECTRICAL APPLIANCE, BASIC SAFETY PRECAUTIONS SHOULD BE FOLLOWED INCLUDING:

1. Always place the humidifier on a firm, flat and level surface. It may not work properly on an uneven surface.
2. Place the humidifier in an area where it is not accessible to children.
3. Do not place the humidifier near any heat sources such as stoves, radiators and heaters.
4. Before using the humidifier, check the power cord for any signs of damage. If the cord is found to be damaged, **DO NOT USE** and return the humidifier to Duracraft under the warranty agreement for repair.
5. This product is equipped with a polarized AC-line plug (a plug having one blade wider than the other). This plug will fit into the power outlet only one way. **This is a safety feature. NEVER** connect the humidifier to any power source other than a 120V AC polarized outlet. If you are unable to insert the plug fully into the outlet, try reversing the plug. If the plug should still fail to fit, contact an electrician to replace the obsolete outlet. **DO NOT defeat the safety purpose of the polarized plug.**

6. The humidifier should always be unplugged and emptied when not in operation or while being serviced or cleaned.

7. Never tilt or attempt to move the humidifier while it is operating or filled with water. **UNPLUG** the humidifier before moving.

8. This humidifier requires regular cleaning. Refer to the CLEANING instructions provided. Never clean the humidifier in any manner other than as instructed in this manual.

9. Turn the humidifier OFF if the relative humidity exceeds 60%, or if you notice moisture on the inside of your windows. For proper humidity readings use an hygrometer which is available in many hardware and department stores, or by ordering one from Duracraft (see Replacement Parts and Care Products).

This humidifier was designed to produce an output of 4 gallons (15.1 litres) over a period of 24 hours; it will cover an area of 1,765 sq. ft. (164 m²) — a room or area approximately 35' x 50' (10.7m x 15.2m)*.

*Area covered and running time depend on quality of construction and insulation.

INTRODUCTION

Thank you for purchasing the DURACRAFT® MODEL DH-831 Natural Cool Moisture™ HUMIDIFIER with removable water tank.

Before using your humidifier, we would like to explain the benefits of maintaining your home or office at the proper humidity level.

HEALTH

Your body needs moisture to stay healthy and comfortable. Dry air can be damaging and irritating. The Duracraft® Natural Cool Moisture™ Humidifier can help relieve:

- Dry, itchy skin and chapped lips.
- Cold symptoms and congestion.
- Dry, scratchy throat and coughs.

For serious medical conditions, always consult your physician prior to use.

ENVIRONMENT

Maintaining the proper moisture level in your home or office with your Duracraft® Natural Moisture™ Humidifier will also:

- Replace needed moisture in furniture.
- Keep indoor plants moist and healthy.
- Eliminate cracking and dryness in wood furniture and fixtures.
- Minimize static electricity.

HOW DOES IT WORK?

Dry air is pulled through the Natural Cool Moisture™ system and a quiet fan disperses invisible, moisture-balanced air. Unwanted minerals and bacteria from the water are trapped inside the Natural Cool Moisture™ filter. There is no “mist” or excessive condensation emitted.

Duracraft's® exclusive Automatic Moisture Balance System™ increases moisture output when the air is dry and lowers the moisture output when the humidity level is high. This automatically adjusts the output for maximum comfort and helps prevent condensation.


SET UP

- Select a firm, level, flat location — at least six inches (15 cm) from any wall for proper air flow and convenient to an electrical outlet.
- Place the humidifier on a water-resistant surface, as water can damage furniture and some flooring. **Duracraft® will not accept responsibility for property damage caused by water spillage.**


FILLING

We recommend that the humidifier be disinfected prior to first use. Please see CLEANING instructions.


- Remove the Water Tank by grasping handle and pulling straight up. Set aside (Fig. 1).



- Remove the Upper Motor Housing from the Reservoir Base, being careful not to let the power cord drop into the base (Fig. 2).




- Remove the Natural Cool Moisture™ filter from its frame in the Reservoir Base (Fig. 3). Run it under cold water; this will help reduce residue build-up. Turn the filter upside down before repositioning it in its frame. Replace in the humidifier. To help extend the life of your filter, repeat this step every time you fill your humidifier.



- Turn the Water Tank upside-down so that the fill cap is facing up; unscrew the fill cap by turning it counter-clockwise.

- Fill the tank with COOL tap water (Fig. 4). Distilled water is not necessary as the water is filtered by the Natural Cool Moisture™ filter. **DO NOT USE HOT WATER.**



- Replace the fill cap by turning it clockwise. **DO NOT OVER TIGHTEN.**

NOTE: WHEN CARRYING THE FILLED WATER TANK, PLEASE USE THE HANDLE AND PLACE YOUR OTHER HAND UNDER THE TANK FOR ADDITIONAL SUPPORT.

FILLING cont.

- Position the Upper Motor Housing back into the Reservoir Base.
- Position the Water Tank back into the humidifier and secure into place.
- Some water will empty into the Reservoir Base when the filled Water Tank is properly positioned.
- Once the filled tank has been positioned, do not attempt to move the humidifier. If it has to be moved, unplug the humidifier and remove the Water Tank first.

NOTE: DO NOT POUR WATER INTO THE GRILL ON THE TOP OF THE UPPER MOTOR HOUSING. DOING SO MAY DAMAGE THE HUMIDIFIER OR CAUSE PERSONAL INJURY.

OPERATION

- With the power switch in the OFF position, plug the filled humidifier into a polarized 120V outlet.

• **DO NOT FORCE THE POLARIZED PLUG INTO THE OUTLET;** it will only fit one way.

CAUTION: DO NOT PLUG IN THE HUMIDIFIER WITH WET HANDS AS AN ELECTRIC SHOCK COULD OCCUR.

- Slide the Humidity Level (Humidistat) knob to HIGH.
- Set the moisture output control to the desired position:
 - HIGH for fast humidifying or NORMAL for quieter operation.

NOTE: IF THE HUMIDIFIER FAN WILL NOT START OR RESTART WHEN YOU SELECT A FAN SPEED, THE HUMIDISTAT MAY BE SET TOO LOW. MOVING THE HUMIDITY LEVEL KNOB TO A HIGHER SETTING SHOULD START THE FAN.

- The length of time your humidifier runs will vary depending on the quality of construction and insulation of your room or house, as well as the fan speed.

- Adjust the round air outlet grill on the top of the Upper Motor Housing (above the fan) to direct moisture in the desired direction. **DO NOT** aim the moisture flow toward furniture or walls that could be damaged by excessive moisture.

- When a comfortable humidity level is reached, lower the Humidity Level (Humidistat) setting slowly until the fan stops. The **DESIRED HUMIDITY** light will then illuminate, indicating that the desired humidity setting has been reached. The Humidistat will automatically restart the fan each time the humidity level falls below this setting. This "ON/OFF" cycle will continue periodically while the humidifier is in use.

- Lower the Humidity Level setting if condensation forms on walls or windows.
- **ALWAYS** be sure to discard any unused water in the base each time you refill the Water Tank or finish using the humidifier.

CLEANING

We recommend that you clean the humidifier once a week, or more often if you:

- have hard water,
- notice a build-up of impurities, or
- detect unpleasant odors.


Using DuraSept™ Humidifier Bacteriostatic Treatment (#AC-802) will help control the growth of bacteria, algae, and odors and help extend the life of the Natural Cool Moisture™ Filter.

NOTE: THE USE OF OTHER WATER TREATMENT PRODUCTS MAY CAUSE DETERIORATION OF THE FILTER OR DAMAGE THE HUMIDIFIER, THEREBY HINDERING THE HUMIDIFIER'S EFFECTIVENESS.

DO NOT USE SOAP, DETERGENTS, OR ABRASIVE CLEANSERS.

Cleaning involves two steps: SCALE REMOVAL and DISINFECTING. Be sure to perform these in the proper order to avoid harmful chemical interactions.

- First, turn off and unplug the humidifier.
- Remove the Water Tank by grasping the handle and pulling straight up.
- Lift the Upper Motor Housing from the Reservoir Base.
- Remove the Natural Cool Moisture™ Filter from its frame (Fig. 5).



- Discard any residual water from the base.

STEP ONE: WEEKLY SCALE REMOVAL (RESERVOIR BASE)

- Fill the Reservoir Base with DuraRinse™ Humidifier Cleaner (#AC-816), following bottle instructions, or one 8-oz. cup (250 ml) of undiluted white vinegar. Let solution stay for 20 minutes.

• With DuraRinse™ or vinegar still in the unit, clean all interior surfaces of the base with a soft brush or cloth to remove scale.

- Rinse Reservoir Base thoroughly with clean, warm water to remove scale and cleaning solution.

STEP TWO: WEEKLY DISINFECTING (WATER TANK AND RESERVOIR BASE)

- Be sure the Water Tank is empty. Fill with water and DuraRinse™ Humidifier Cleaner (#AC-816), following bottle instructions, or 1 teaspoon chlorine bleach in 1 gallon (4 litres) water. Let solution stay 20 minutes, swishing every few minutes to wet all surfaces.
- Empty tank after 20 minutes. Rinse with water until bleach/solution smell is gone.
- Repeat for the Reservoir Base.

AFTER DISINFECTING...

- Clean all surfaces of the Upper Motor Housing with a dry, soft cloth. **DO NOT USE WATER TO CLEAN THE UPPER MOTOR HOUSING. THIS MAY DAMAGE THE HUMIDIFIER OR CAUSE ELECTRIC SHOCK.**

- If you have hard water you may need to clean or change the filter more often. If the filter is dirty, rinse it under cold tap water and turn the filter upside down before repositioning it in the frame. Do not squeeze or wring out pad. Do not soak pad in bleach or vinegar. When the filter turns dark brown, replace it. Using DuraSept™ Humidifier Bacteriostatic Treatment will help extend the life of the filter. For best and proven results, always use Duracraft® Natural Cool Moisture™ Filters available from your local store or from Duracraft.

- Reposition the Filter Frame, Upper Motor Housing, and Water Tank.

NOTE: THE FAN MOTOR OF THIS HUMIDIFIER AND THE NATURAL COOL MOISTURE™ FILTER ARE DESIGNED TO FUNCTION EFFICIENTLY AS A SET. USING ANY OTHER FILTER COULD DAMAGE THE HUMIDIFIER'S MOTOR OR IMPAIR ITS PERFORMANCE.

END-OF-SEASON CARE AND STORAGE

- Follow weekly CLEANING instructions at end of humidification season or when humidifier will not be used for at least one week or more.

- Remove and throw away filter; do not store with a used filter (**SAVE THE FILTER FRAME FOR USE WITH YOUR REPLACEMENT FILTER PAD**).

- Let the humidifier dry completely before storing. Do not store with water inside the Reservoir Base or Water Tank.

- Pack the unit in its original carton and store in a cool, dry location.

- Remember to install a new filter and clean the humidifier at the start of the next humidification season.

ELECTRICAL RATINGS

This product is rated 0.45 amps at 120V, 60 Hz.

NOTE: IF YOU EXPERIENCE A PROBLEM WITH YOUR HUMIDIFIER'S UPPER MOTOR HOUSING, PLEASE SEE THE WARRANTY FOR INSTRUCTIONS. PLEASE DO NOT ATTEMPT TO OPEN OR REPAIR THE UPPER MOTOR HOUSING YOURSELF. DOING SO WILL VOID THE WARRANTY

AND COULD CAUSE DAMAGE OR PERSONAL INJURY. IF THE PROBLEM STILL PERSISTS, PLEASE CALL:

DURACRAFT CORP.
CUSTOMER SERVICE
DEPARTMENT

TOLL FREE: 1-800-554-4558

Business Hours:
Monday – Friday
8:00 AM – 10:00 PM (EST)

Weekends
8:30 AM – 5:00 PM (EST)

Mail questions or comments to:

DURACRAFT CORP.
Customer Service Dept.
250 Turnpike Road
Southborough, MA 01772
U.S.A.

Please be sure to specify model number.

CARE PRODUCTS

Model AC-802 — DuraSept™ Humidifier Bacteriostatic Treatment helps control the growth of bacteria and algae in your humidifier and helps prevent unpleasant mildew odors. It can also extend the life of the Natural Cool Moisture™ Filter. For best results, DuraSept™ should be added every time you fill your humidifier.

Model AC-816 — DuraRinse™ Humidifier Cleaner helps soften lime scale and mineral deposits when cleaning the Natural Cool Moisture™ Humidifier. DuraRinse™ should be used whenever you begin to notice discoloration in the humidifier's reservoir or water tank.

Model AC-817 — DuraFree™ Humidifier Water Softener softens hard water impurity


deposits in the reservoir and on the Natural Cool Moisture™ Filter so they can be easily rinsed away.

Model AC-850 — Humidifier Complete Care Kit. A complete care kit for your Natural Cool Moisture™ Humidifier, including one 32-oz. (946 ml) bottle of each of the above products: DuraSept™, DuraRinse™ and DuraFree™.

REPLACEMENT PARTS AND CARE PRODUCTS

Item	Model No.	Price U.S.	Price Can.
Natural Cool Moisture™ Replacement Filter	AC-818	\$ 14.99	\$20.25
DuraFree™ Humidifier Water Softener (32 oz./946ml)	AC-817	\$ 5.00	\$ 6.75
DuraRinse™ Humidifier Cleaner (32 oz./946ml)	AC-816	\$ 5.00	\$ 6.75
DuraSept™ Humidifier Bacteriostatic Treatment (32 oz./946ml)	AC-802	\$ 5.00	\$ 6.75
Humidifier Complete Care Kit	AC-850	\$14.00	\$18.50
Hygrometer (measures room humidity level)	AC-900	\$14.99	\$20.25
Water Tank	DH-831-1	\$15.99	\$21.50

To order replacement parts or care products, complete and mail the enclosed Order Form. Be sure to include a check or money order payable to Duracraft Corporation or call the Duracraft Customer Service Department on our toll-free number: 1-800-554-4558. VISA, MASTERCARD or DISCOVER are accepted. The above prices do not include shipping charges or sales tax where applicable.



ORDER FORM FOR MODEL DH-831

REPLACEMENT PARTS AND CARE PRODUCTS

If your local dealer is out of stock, Duracraft replacement parts and care products may be ordered directly. Fill out the form and mail it along with a check or money order (no cash, please) to Duracraft Corp. at the address shown below. Please allow four weeks for delivery. Massachusetts residents add 5% Sales Tax. Please add 7% G.S.T. plus applicable provincial taxes.

Item	Item No.	Quan.	Price U.S.	Price Can.	Total
Natural Cool Moisture™ Replacement Filter	AC-818		\$ 14.99	\$20.00	
DuraFree™ Humidifier Water Softener (32 oz./946 ml)	AC-817		\$ 5.00	\$6.75	
DuraRinse™ Humidifier Cleaner (32 oz./946 ml)	AC-816		\$ 5.00	\$6.75	
DuraSept™ Humidifier Bacteriostatic Treatment (32 oz./946 ml)	AC-802		\$ 5.00	\$6.75	
Humidifier Complete Care Kit	AC-850		\$14.00	\$18.50	
Hygrometer (measures room humidity)	AC-900		\$14.99	\$20.00	
Water Tank	DH-831-1		\$15.99	\$21.50	

Parts and accessories subject to availability.
Prices may change without notice.

CHECK OR MONEY ORDER
ENCLOSED. NO COD'S ACCEPTED.

SEND TO:

Duracraft Corporation.
Customer Service Department
250 Turnpike Road
Southborough, MA 01772 U.S.A.
Attn: Customer Service Department

or for MasterCard, Visa or Discover orders:

Cardholder name (please print): _____

Cardholder signature: _____

Card Number: _____ Expiration Date: _____

Please Check: MasterCard Visa Discover

SUBTOTAL	
7% G.S.T. & applicable provincial taxes	
MA Residents add 5% Sales Tax	
Shipping and Handling	\$ 4.50 U.S. \$ 6.00 Can.
TOTAL ENCLOSED	

Name _____

Address _____

Day time phone no. (_____) _____

In case we need to contact you about your order.

LIMITED WARRANTY

DURACRAFT
4 Gallon (15.1 Litre)
Output Per Day

DURACRAFT®
NATURAL COOL
MOISTURE™ HUMIDIFIER

This product has been engineered and crafted with great care for your satisfaction.

Please read all instructions before attempting to use this product. **Be sure to fill out and return the enclosed card within 7 days of purchase.**

A. This 5 year limited warranty applies to repair or replacement of product found to be defective in material or workmanship. This warranty does not apply to damage resulting from commercial, abusive, unreasonable use or supplemental damage. Defects that are the result of normal wear and tear will not be considered manufacturing defects under this warranty. Duracraft is not liable for incidental or consequential damages of any nature. Any implied warranty of merchantability or fitness for a particular purpose on this product is limited in duration to the duration of this warranty. Some regions do not allow the exclusion or limitation of incidental or consequential damages, or limitations on how long an implied warranty lasts, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you also may have

other rights which vary from region to region. This warranty applies only to the original purchaser of this product.

B. At its option Duracraft will repair or replace this product if it is found defective in material or workmanship. Defective product should be returned directly to Duracraft.

C. This warranty does not cover damage resulting from any unauthorized attempts to repair or from any use not in accordance with this manual.

D. Return defective product to the following address with a brief description of the problem. Include proof of purchase and a U.S. \$10.00/Can.\$13.50 check or money order for handling, return packing and shipping charges. Please include your name, address and a daytime phone number. You must prepay shipping charges. Mark carton "Attention Repair Department." Ship to:

Duracraft Corp.
Southpoint Distribution Center
4755 Southpoint Drive
Memphis, TN 38118
U.S.A.

NOTE: THIS WARRANTY DOES NOT COVER THE NATURAL COOL MOISTURE™ FILTER, WHOSE PERFORMANCE WILL DEPEND UPON THE CONDITION OF THE WATER USED IN THE HUMIDIFIER.

